



**2010 Bluegrass Pulling Series
Rules & Regulations
10,000LB HOT FARM TRACTORS
Class Representatives: Robert Mobley – Loren Glass**

1. Must have steel flywheels.
2. 20.8 – 38 max tire size (no cut tires).
3. All tractors must be equipped with a deadman throttle.
4. Roll cages or OEM FACTORY ROPS are mandatory.
5. Seat belts and helmets are mandatory.
6. Must run stock diesel fuel only, no alcohol, methanol, nitrous or propane assist or any other compressed gas allowed (DIESEL FUEL ONLY).
7. All tractors must be equipped with an AIR SHUT-OFF engine kill switch, it is also recommended but (optional) that this kill switch work from the driver seat as well as the sled.
8. 2.75 turbo (measured at the air inlet close to the fan) SLUGS & MATH ENHANCEMENT/E- GROOVES ARE PERMITTED top 3 finishers in each class will be teched after the class is finished. No removable bushings or slugs permitted. Turbo will be teched with a 2755 inch slug. Top 3 finishers must stay near pit area to be teched.
9. All tractors must run OEM intake and exhaust.
10. 20 inches max draw bar height, hitch must measure 20 inches from the center of the rear axle to hitching point. Flat hitches only, hitch must be at least 1 inch thick from all directions from hitching point must be at least 3 by 4 inch hole. No third arm hitches, no clevises.
11. All tractors must run factory appearing injection pumps or an A pump. Fuel system must comply with make and model of tractor, **no P-pumps**.
12. All tractors are to look standard for its year make and model in appearance, all major factory sheet metal is required.
13. Side shields are optional.
14. No weight beyond 24 inches of the most forward point of the tractor. All weight brackets must be stationary.
15. Steel or cast steel hubs only, no pure cast hubs.
16. Tractor must have electric fan or 60 thousand shroud around fan.
17. WATER INJECTION Permitted (water only, no alcohol, ethanol, nitro methane, etc). NO INTERCOOLERS.
18. Mandatory wheelie bars, must have 5 x 5" pad, no more than 10 inches from the ground. Must be 3 inches back from farthest point of rear tire to front of the pad.
19. One driver per tractor per class. All drivers must sign a release form.
20. 470 Cubic inch limit
21. This is a 3000 RPM class.