



2010 Bluegrass Pulling Series Rules & Regulations

2.8 – 3.0 Outlaw Street Diesel Trucks

1. 8000 pound maximum weight for 2.8 trucks, 3.0 trucks will be 7500 lb
2. DOT street legal tires. No chains, cut tires, or studs. 35" Maximum diameter.
3. Single or Dual wheels are allowed.
4. Manufactured style flat bed or factory bed.
5. Weight bracket must be fastened to both sides of frame support.
6. Hitch support must be fastened at top, no further than center of rear axle.
7. Must have an air shutoff, no butterfly style shutoffs
8. 2.8/3.0 Turbo size - bushings allowed.
9. 26" hitch height. Hook point will be at rear bumper or Reese hitch location. Hook point must be the furthest point to the rear of the vehicle and a minimum of 44 inches from the center of the rear axle NO under-bed pulling hitches permitted.
10. **All true 3.0 trucks will be permitted to follow modified chassis rules excluding tires and turbo.** No tube chassis's or fiberglass bodies.
11. No alcohol, nitrous oxide, or propane injection.
12. Engine must be derived stock from the factory in a one ton pickup truck or less application. Engine does not have to be the same manufacturer as the truck. For example: A Cummins engine may be transplanted in a Ford or Chevy truck.
13. Front hanging weights are allowed, but not to exceed 60 inches forward of the center of the front axle.
14. Drive train must be OEM from one ton or less pickup truck. For example: no drop boxes or reversers.
15. Rear suspension may be blocked. Blocks must be easily removed and no solid suspensions on 2.8 trucks. Axle bolts must be covered.
16. Trucks with manual transmissions, running in excess of 4000 rpm's, must run a scatter proof blanket on the bell housing.
17. Two 3/8" bolts must be through the exhaust in a cross pattern as close to the turbocharger as possible
18. Must have U-joint shields at least 6" long around rear U-joint.
19. Driver must wear a seatbelt.
20. All trucks must have fuel shutoffs, kill switches and driveline loops
21. Exhaust must exit upward only.

22. Helmet and SFI approved jackets are recommended for 2.8 trucks, SFI approved Fire-suits are mandatory for 3.0 trucks
23. Working Fire Extinguishers are mandatory.
24. 2.8 trucks must run an OEM transmission and transfer case.
25. 3.0 trucks can run an open driveline. Any front axle, any transfer case and any rear axle. No planetaries permitted.