

2017 Battle of the Bluegrass Rules for 8500LB Pro Farm Tractor

Class Representative: Byron Amburgey

No Rule Changes from 2016

Engine:

1. 470 cubic inch displacement, Maximum weight of 8500 lb. Turbo- 3" inlet with .250 map groove (KY). No forward-facing map groove. No H5, HX80 or S500 Series Turbo. No large frame turbos.
2. NO 8600 series P- pumps.
3. OEM AG rear end.
4. Aluminum heads are not allowed. OEM Only (no recast heads).
5. Only two (2) valves per cylinder.
6. Fuel Pump- any pump maximum P-pump. P3000 or P7100
7. Water injection allowed; water with oil lubricant only.
8. OEM intake and exhaust manifolds only. NO homemade manifolds allowed.
9. NO intercoolers or after-coolers permitted.
10. Intake housing to be no larger than 3 inch at the face of the wheel. Single compressor wheel must protrude into 3 inch bore at least 1/8". Stock map width enhancement is permitted.
11. We also have Indiana rules for IN Hot Farm Tractors. (For details, contact Kevin Fulks 859-391-2991)

Sheet Metal and Frame:

1. Front weights shall not extend more than 13 feet from the center of the rear axle.
2. Maximum wheelbase of 114 inches.
3. No components tractors allowed.

Fuel:

1. No compressed air, nitrous oxide, fuel conversions, propane or nitro methane allowed. The only exception is the use of starting aid.
2. Diesel fuel will be the only fuel accepted.
3. No oxygen carries or combustion accelerators allowed in fuel.

Tires:

Maximum tire size of 20.8 (Cut or uncut) at 8500 lb.

Hitch:

1. Minimum hitch length of 18 inches measured from the center of the rear axle. Can be no closer.
2. Maximum hitch height of 20 inches.
3. Hitch shall remain stationary in all directions.

General Rules:

All vehicles/drivers must comply with general rules.

OB