

# 2017 Battle of the Bluegrass Rules for B Series Class: Super Stock 4x4 Small Block

This class is 4x4 small block class.

**Weight: 6000lb**

This is a class name change from the Hot Street 4WD Small Block Class

**No rule changes from 2016.**

1. No dry sump motors.
2. **No nitrous oxide allowed.**
3. Frame must be OEM.
4. Solid suspensions allowed in rear.
5. Hanging weights allowed. No point weight box to exceed 60" from center of front differential - small tow hook or D ring allowed for towing purposes.
6. Hitch height 26". Hitch hole must be 3 wide by 3 1/2 " long.
7. Hitch point must be at least 36% of wheelbase, measure from center of rear differential to back of hole.
8. Open headers allowed, upright okay.
9. Aluminum intake allowed, no tunnel rams.
10. Carburetor limited to one 4 barrel 4150. No fuel injection. Adapters allowed up to 2". dual line maximum.
11. Tires must be DOT legal, no larger than 33 x 12.50.
12. Must have SFI safety approved bell housing or blanket IF automatic SFI approved harmonic balancer or cover. Must have fender wells if not shields to cover the motor.
13. Must be naturally aspirated, racing fuel only, no nitrous oxide, no alcohol, no mixes.
14. Must have drive shaft loops to cover each universal joint.
15. Helmets are mandatory.
16. Must have kill switch.
17. One ton rear ends only. No military rear ends.
18. Aluminum heads - degree on heads are stock degree for OEM heads: 18 degree - Dodge; 19 degree - Ford; 23 degree - Chevy. No aluminum blocks.
19. Wheelbase max is 134"
20. Must have fire extinguisher.
21. Engine is 450 cubic inch limit.
22. New rule 2015: OEM Body swaps allowed. i.e 56 chevy can run on a 86 chevy chassis.
23. New rule 2015 No air bags or air shocks
24. New rule 2015 No LS motors (12 degree heads) at this time.
25. The rear of engine block to center of front axle can be no less than 12 inches.
26. **BOB tech official will have final say so in agreement of two BOB officials.**
27. All vehicles/drivers must comply with general rules.